

HIS VGA Product line

www.hisdigital.com



**HIS HD 3870X2 HDMI
Dual DL PCIE**

- > Powered by dual Radeon HD 3800 GPU @ 825MHz
- > 1GB(512bit) GDDR3 memory @ 1800MHz
- > 2 x 256-bit memory interface
- > DirectX 10.1 / Shader Model 4.1 support
- > ATI CrossFireX support



HIS HD 3870 IceQ 3 PCIE

- > Powered by Radeon HD 3800 GPU @ 775MHz
- > 512MB(256bit) GDDR4 memory @ 2252MHz
- > HIS IceQ 3 Cooling Technology
- > 256-bit memory interface
- > ATI CrossFireX support



**HIS HD 3850 HDMI
Dual DL PCIE**

- > Powered by Radeon HD 3800 GPU @ 668MHz
- > 512MB (256bit) GDDR3 memory @ 1656MHz
- > 256-bit memory interface
- > ATI CrossFireX support



**HIS HD 3650 iCooler II
PCIE**

- > Powered by Radeon HD 3600 GPU @ 725MHz
- > 512MB (256bit) GDDR3 memory @ 1656MHz
- > 128-bit memory interface
- > HIS iCooler II Cooling Technology
- > ATI CrossFireX support



**HIS HD 3450 Silence
PCIE**

- > Powered by Radeon HD 3400 GPU @ 600MHz
- > 256MB(64bit) DDR2 memory @ 800MHz
- > HIS iFan Cooling Technology
- > 64-bit memory interface
- > ATI CrossFireX support




**HIS HD 2400 PRO
256MB PCIE**

- > ATI Radeon HD 2400 PRO GPU - 525MHz
- > 256MB-64bit DDR2 memory - 800MHz
- > Built-in HDMI with HDCP and 5.1 surround audio



**X1550PCie_iFan_Card_
512MB PCIE**

- > Powered by ATI Radeon X1550 - 550MHz
- > 512MB-64bit 4 channel DDR2 memory - 800MHz
- > ATI CrossFireX support



**X1550PCie_iFan_Card_
256MB PCIE**

- > Powered by ATI Radeon X1550 - 550MHz
- > 256MB-64bit 4 channel DDR2 memory - 800MHz
- > ATI CrossFireX support



HIS HD 3850 AGP

- > Powered by Radeon HD 3800 GPU @ 668MHz
- > 512MB(256bit) GDDR3 memory @ 1656MHz
- > 256-bit memory interface
- > ATI CrossFireX




**HIS HD 2600PRO Fan
Dual DL AGP**

- > Powered by Radeon HD 2600 XT GPU - 800MHz
- > 512MB 128-bit DDR2 - 800MHz
- > Built-in HDMI and 5.1 surround audio



**HIS HD 2600XT Fan
512MB AGP**

- > Powered by Radeon HD 2600 PRO GPU - 600MHz
- > 512MB 128-bit GDDR3 - 1400MHz
- > Built-in HDMI and 5.1 surround audio



HIS 9259 256MB PCI

- > Powered by ATI Radeon 9250 VPU - 240MHz
- > 256MB-128bit DDR memory - 400MHz



**HIS HD 4850 HDMI
512MB PCIE**

- > Powered by ATI Radeon HD 4850 GPU - 625MHz
- > 512MB -256bit GDDR 3 memory @ 1986MHz
- > DUAL DL-DVI & TV (HDCP) support
- > DirectX 10.1 support
- > ATI CrossFireX support
- > PCI Express 2.0 support
- > Full HD 1080p



**HIS HD 4870 HDMI
512MB PCIE**

- > Powered by ATI Radeon HD 4870 GPU - 750MHz
- > 512MB -256bit GDDR 5 memory @ 3600MHz
- > DUAL DL-DVI & TV (HDCP) support
- > DirectX 10.1 support
- > ATI CrossFireX support
- > PCI Express 2.0 support
- > Full HD 1080p